3S LIGHTING PRODUCT DATASHEET

Brillio 130 C

Product Family: Brillio
Product SKU: 2B150 Internal Code:

OSRAM



Dimensions (mm) 130 (D) 780 (H)
Weight (kg)

PRODUCT FEATURES

Aesthetics / Use	Round, Symetrical, LED Bollard, for exterior applications, featuring Osram LED as standard,
Luminaire Housing	Aluminium body,powder-coated as standard
Fixing Method	Aluminium base
Reflector / Optics	Cone shaped diffuser,
Heatsink / Other	Supplied with efficient passive aluminium heatsink
Control Gear	Integral non-dim / dim driver,supplied with terminal block inside
Max. Ambient Temp.	

IP RATING

☐ IP65

DRIVER CONTROL

☐ Non Dim IP65+ Integral

PAINT FINISH

☐ Matt Black Textured
☐ Matt Dark Grey Textured
☐ Custom

SECONDARY PAINT FINISH

We reserve the right to make technical changes without prior notice 3S lighting Pty Ltd

Brillio 130 C

Product Family: Brillio
Product SKU: 2B150 Internal Code:

LED PERFORMANCE

System Power (W) - LED Luminous Flux (lm) - CRI - CCT (K) - (internal code)

Note: To obtain System Flux (lm) multiply LED Luminous Flux with LOR (Luminaire Output Ratio)
System Flux = LED Luminous Flux × LOR - e.g. 1414lm × 0.6361 = 899lm System Flux

CRI 80+

☐ 14.0W - 1733lm - CRI80 - 3000K - (873)

☐ 14.0W - 1849lm - CRI80 - 4000K - (874)

We reserve the right to make technical changes without prior notice 3S lighting Pty Ltd

3S LIGHTING PRODUCT DATASHEET

Brillio 130 C

Product Family: Brillio
Product SKU: 2B150 Internal Code:

BEAM / OPTICAL OPTIONS

☐ **B180P120 - IP65**

Indirect_Sym - 127 DEG

Metalized Reflector + Clear PMMA Diffuser

LOR : 40% (0.3982)



S3 LIGHTING LTD • 13 KANGOO RD SOMERSBY NSW 2250 • PO BOX 6167 WEST GOSFORD NSW 2250
ph. 02 4340 4300 • fax. 02 4340 4343 •info@3slighting.com•www.3slighting.com
We reserve the right to make technical changes without prior notice 3S lighting Pty Ltd