

Product No.	System Power*	LED Lumen	Beam Angle	Mounting	Colour Temp	CRI	Driver
305219.000	17W	2000Lm (15.2W)	Omni-Directional	Inground Mounted	4000K	80+	700mA



LIGHTSOURCE BY
XICATO

■ **Product Features**

- Dome top white louvred inground mounted bollard
- High quality die cast aluminium, extruded aluminium and stainless steel
- Protection class IP54
- Clear UV stabilised Polycarbonate diffuser
- Supplied complete with electronic LED driver
- Bayonet locking head with locking grub screw
- Inground mounted bury a minimum of 200mm, maximum of 300mm
- Finish: 3S Black, 3S Silver optional
- *Connected electrical loads are rated values and subject to a tolerance of +/- 10%


■ **Product Dimensions**



■ **Product Standard**



■ **Product Options**



■ Luminaire Specification

Product No.	Beam Angle	LED Module	LED Output	System Power	Colour Temp	Driver	Trim Colour
305219.XYZ	Omni-Directional	<input type="checkbox"/> XTM STD (CRI 80+)	1300lm	11.4W	<input type="checkbox"/> 2700K	<input type="checkbox"/> NON-DIM	<input type="checkbox"/> 3S WHITE
		<input type="checkbox"/> XTM STD (CRI 80+)	2000lm	18.24W	<input type="checkbox"/> 3000K	<input type="checkbox"/> DALI	<input type="checkbox"/> 3S BLACK
		<input type="checkbox"/> XTM STD (CRI 80+)	2100lm	19.8W	<input type="checkbox"/> 3500K		<input type="checkbox"/> 3S SILVER
					<input type="checkbox"/> 4000K		<input type="checkbox"/> CUSTOM

■ Luminaire Configuration

Connectivity	<input type="checkbox"/> Casambi	<input type="checkbox"/> Tridonic basicDIM Wireless	<input type="checkbox"/> XICATO GalaXi
--------------	----------------------------------	---	--

■ Luminaire Information

LED Module	Standard XTM19*		
CRI	80+*		
LED Lumen	1300lm	2000lm*	2100lm
Current	700mA	700mA*	700mA
Typical LED Wattage	9.5W	15.2W*	16.5W
LED Efficacy	137lm/W	131lm/W*	127lm/W
Overall Height "H"	1180mm	1180mm*	1180mm

"XYZ" - Part No. to be advised by 3S Lighting based on the combination of configurable options selected

A.XYZ - "A" of the Part No. determined by the beam angle selected

* Standard product specification

■ Project Information

Project Name:		Type:	
Quantity:		Expected Due Date:	
Client's Name:		Date of Issue:	
Notes:		Signature:	

■ XICATO Light Source



Initial Colour Consistency: ≤ 1 x 2 MacAdam Ellipses (SDCM) at 70°C, B0
Lumen Maintenance: L70/B0 at 50,000 hours

Colour Maintenance: Consistency maintained < 0.003 Δu'v' at 50,000 hours

Warranty: 5 years for individual modules (B0) on mortality, color and lumen maintenance.

Standard XTM19 Excellent, natural colour rendition with high efficiency.

Designer XTM19 An optimal balance between accurate, natural colour rendition, lumen output and efficacy.

Artist XTM19 The most accurate, natural colour rendition possible, over the entire visual spectrum.

[... click for more information](#)

■ APPs (with XID / TBW driver only)



CASAMBI, Tridonic basicDim Wireless and XICATO GalaXi

Lighting control solutions provide for all the control options that are expected from a full featured professional lighting control solution, Apps available for both iOS and Android.

[... click for more information](#)