

Product No.	System Power*	LED Lumen	Beam Angle	Mounting	Colour Temp	CRI	Driver
<b>305109.000</b>	18.2W	2000Lm (15.2W)	Omni-Directional	Surface mounted	4000K	80+	700mA




LIGHTSOURCE BY  
**XICATO®**

■ **Product Features**

- Flat top white louvred surface mounted bollard
- High quality die cast aluminium and stainless steel
- Protection class IP54
- Clear UV stabilised Polycarbonate diffuser
- Supplied complete with highly efficient heat sink and electronic LED driver
- Bayonet locking head with locking grub screw
- Finish: 3S Black, 3S Silver optional
- 180Deg Shield available on request
- \*Connected electrical loads are rated values and subject to a tolerance of +/- 10%

■ **Product Dimensions**



■ **Product Standard**



■ **Product Options**



■ Luminaire Specification

Product No.	Beam Angle	LED Module	LED Output	System Power	Colour Temp	Driver	Trim Colour
305109.XYZ	Omni-Directional	<input type="checkbox"/> XTM STD ( CRI 80+)	1300lm	11.4W	<input type="checkbox"/> 2700K	<input type="checkbox"/> NON-DIM	<input type="checkbox"/> 3S WHITE
		<input type="checkbox"/> XTM STD ( CRI 80+)	2000lm	18,24W	<input type="checkbox"/> 3000K	<input type="checkbox"/> DALI	<input type="checkbox"/> 3S BLACK
		<input type="checkbox"/> XTM STD ( CRI 80+)	2100lm	19.8W	<input type="checkbox"/> 3500K		<input type="checkbox"/> 3S SILVER
					<input type="checkbox"/> 4000K		<input type="checkbox"/> CUSTOM

■ Luminaire Configuration

Connectivity	<input type="checkbox"/> Casambi	<input type="checkbox"/> Tridonic basicDIM Wireless	<input type="checkbox"/> XICATO GalaXi
--------------	----------------------------------	---	--

■ Luminaire Information

LED Module	Standard XTM19*		
CRI	80+*		
LED Lumen	1300lm	2000lm*	2100lm
Current	700mA	700mA*	700mA
Typical LED Wattage	9.5W	15.2W*	16.5W
LED Efficacy	137lm/W	131lm/W*	127lm/W
Overall Height "H"	1000mm	1000mm*	1000mm

"XYZ" - Part No. to be advised by 3S Lighting based on the combination of configurable options selected

A.XYZ - "A" of the Part No. determined by the beam angle selected

\* Standard product specification

■ Project Information

Project Name:		Type:	
Quantity:		Expected Due Date:	
Client's Name:		Date of Issue:	
Notes:		Signature:	

■ XICATO Light Source



**Initial Colour Consistency:** ≤ 1 x 2 MacAdam Ellipses (SDCM) at 70°C, B0  
**Lumen Maintenance:** L70/B0 at 50,000 hours

**Colour Maintenance:** Consistency maintained < 0.003 Δu'v' at 50,000 hours

**Warranty:** 5 years for individual modules (B0) on mortality, color and lumen maintenance.

**Standard XTM19** Excellent, natural colour rendition with high efficiency.

**Designer XTM19** An optimal balance between accurate, natural colour rendition, lumen output and efficacy.

**Artist XTM19** The most accurate, natural colour rendition possible, over the entire visual spectrum.

[... click for more information](#)

■ APPs (with XID / TBW driver only)



CASAMBI, Tridonic basicDim Wireless and XICATO GalaXi

Lighting control solutions provide for all the control options that are expected from a full featured professional lighting control solution,

Apps available for both iOS and Android.

[... click for more information](#)