

Product No.	System Power*	LED Lumen	Beam Angle	Mounting	Colour Temp	CRI	Driver
<b>305319.000</b>	18W	2100Lm (16.5W)	Indirect	Inground Mounted	4000K	80+	700mA



LIGHTSOURCE BY  
**XICATO®**

■ **Product Features**

- High quality die cast aluminium, extruded aluminium and stainless steel
- Bayonet locking cover with locking grub screw
- Protection class IP54
- Fixed top reflector underside satin white for diffused wide and glare free light distribution
- Supplied complete with electronic LED driver
- Clear safety glass
- Finish: S3 Silver, 3S Black optional
- \*Connected electrical loads are rated values and subject to a tolerance of +/- 10%
- Inground mounted bury a minimum of 200mm, maximum of 300mm


■ **Product Dimensions**



■ **Product Standard**



■ **Product Options**



■ Luminaire Specification

Product No.	Beam Angle	LED Module	LED Output	System Power	Colour Temp	Driver	Trim Colour
305319.XYZ	INDIRECT	<input type="checkbox"/> XTM STD ( CRI 80+)	1300lm	11.4W	<input type="checkbox"/> 2700K	<input type="checkbox"/> NON-DIM	<input type="checkbox"/> 3S WHITE
		<input type="checkbox"/> XTM STD ( CRI 80+)	2000lm	18,24W	<input type="checkbox"/> 3000K	<input type="checkbox"/> DALI	<input type="checkbox"/> 3S BLACK
		<input type="checkbox"/> XTM STD ( CRI 80+)	2100lm	19.8W	<input type="checkbox"/> 3500K		<input type="checkbox"/> 3S SILVER
					<input type="checkbox"/> 4000K		<input type="checkbox"/> CUSTOM

■ Luminaire Configuration

Connectivity	<input type="checkbox"/> Casambi	<input type="checkbox"/> Tridonic basicDIM Wireless	<input type="checkbox"/> XICATO GalaXi
--------------	----------------------------------	---	--

■ Luminaire Information

LED Module	Standard XTM19*		
CRI	80+*		
LED Lumen	1300lm	2000lm*	2100lm
Current	700mA	700mA*	700mA
Typical LED Wattage	9.5W	15.2W*	16.5W
LED Efficacy	137lm/W	131lm/W*	127lm/W
Overall Height "H"	1130mm	1130mm*	1130mm

"XYZ" - Part No. to be advised by 3S Lighting based on the combination of configurable options selected

A.XYZ - "A" of the Part No. determined by the beam angle selected

\* Standard product specification

■ Project Information

Project Name:		Type:	
Quantity:		Expected Due Date:	
Client's Name:		Date of Issue:	
Notes:		Signature:	

■ XICATO Light Source



**Initial Colour Consistency:** ≤ 1 x 2 MacAdam Ellipses (SDCM) at 70°C, B0  
**Lumen Maintenance:** L70/B0 at 50,000 hours

**Colour Maintenance:** Consistency maintained < 0.003 Δu'v' at 50,000 hours

**Warranty:** 5 years for individual modules (B0) on mortality, color and lumen maintenance.

**Standard XTM19** Excellent, natural colour rendition with high efficiency.

**Designer XTM19** An optimal balance between accurate, natural colour rendition, lumen output and efficacy.

**Artist XTM19** The most accurate, natural colour rendition possible, over the entire visual spectrum.

[... click for more information](#)

■ APPs (with XID / TBW driver only)



CASAMBI, Tridonic basicDim Wireless and XICATO Galaxi

Lighting control solutions provide for all the control options that are expected from a full featured professional lighting control solution, Apps available for both iOS and Android.

[... click for more information](#)